



Online Form Instructions

- For the purpose of ECI REC online forms, when the word “signature” appears, a typed, legal name is an acceptable substitute. As long as the complete, legal name appears in each blank for which a signature was requested, the form is accurate and binding (pending accurate completion of all other form sections). It is not necessary to print and sign the form if users plan on taking advantage of the “submit by email” option provided on the final page of each form.
- Some rebates may require the actual signatures of mechanical engineers. ECI REC will follow-up with members applying for those rebates as necessary.
- Please do not fill out the “office only” sections of the form. Tab past them when filling out the form.
- Completed forms and required sales receipts or invoices may also be submitted to ECI REC via fax at (319) 443-4359. Please submit both the completed form and accompanying invoice(s) using the same method—fax or email—to ensure they arrive together at ECI REC.

All★ Star Home - Building Checklist

Complete ALL sections below. **PLEASE PRINT.**

Submit this checklist along with a completed copy of the All-Star Home Bonus Incentive form.

Last Name (Homeowner)		Address (Qualifying All-Star Home)		
City	State	Zip	Completion Date	

Type of Construction:

1. New Construction
 2. Efficient Upgrade

House Age (yrs)

Enter installed insulation R-values for the following components that exist in the home. **If a component does not apply, enter NA.**

BUILDING COMPONENT		DESCRIPTION/REQUIREMENTS	Minimum Insulation R-value	Installed R-value
WALLS	Above Grade	Basement walls more than 50% above grade and the box sill of basement must also meet this requirement.	R-21	
	Below Grade	Basement walls more than 50% below grade.	R-10	
	Crawlspace Wall	Required for closed, non-vented crawlspaces.	R-20	
CEILINGS	All Ceiling Types		R-38	
FLOORS	Basement (non-heated floor)	Floor at least 4 feet below grade, otherwise treat as a Slab. For walkout basements see Walkout Slab.	None	NA
	Basement (heated floors)	Insulation required under floor. For walkout basements see Walkout Slab.	R-10	
	Slab	Floors less than 4 feet below grade. Insulation must cover face of slab with rigid foam that extends 4 feet below grade (a combination of vertical and horizontal distance can be used to meet requirement).	R-10	
	Walkout Slab	The edge of floor slab (walkout side) must be insulated with rigid foam extending 4 feet below grade (a combination of vertical and horizontal distance can be used to meet requirement); remaining floor area must still meet requirements for Basement floors.	R-10	
	Floor over Crawlspace	Required for open, non-vented crawlspaces.	R-30	

WINDOWS (Check below to verify requirements are met; provide window information)

- Must be low-E windows and meet Energy Star requirements with a U-value of 0.35 or less. At time of installation, windows should display the Energy Star label or NFRC (National Fenestration Rating Council) label showing the U-value.

Window Brand and Product Line: _____

Window Description: (example: vertical slider) _____

BUILDING LEAKAGE (Check measure used to minimize infiltration of outdoor air)

- Exterior house wrap with all seams taped (eg. Tyvek paper)
 Exterior rigid board insulation (extruded polystyrene or urethane sheathing) with all seams taped
 Other (subject to approval). Describe: _____

Builder Information:

Business Name		
Address		
City	State	Zip Code

Homeowner or Builder Notes:

BUILDER AGREEMENT (Signature Required)	
I agree that all of the above information is true and that it represents the installed measures for the home located at the address shown. I understand that the East-Central Iowa Rural Electric Cooperative reserves the right to inspect the home to verify this information before issuing any rebates to the member.	
Builder Signature	Date